Waterproof Foundation and Improve Drainage for the Fredericksburg Battlefield Visitor Center Photos



Front of the Fredericksburg Battlefield Visitor Center -2020



Front of the Fredericksburg Battlefield Visitor Center – 2020



Rear of the Fredericksburg Battlefield Visitor Center – 2020



American Disabilities Act (ADA) Ramp on the front of the Fredericksburg Battlefield Visitor Center. The ramp was constructed in 1985. It will be removed and rebuilt, but will be 1-2 feet longer and 1-2 feet wider to comply with more recent ADA requirements.



American Disabilities Act (ADA) Ramp on the front of the Fredericksburg Battlefield Visitor Center. The ramp was constructed in 1985. It will be removed and rebuilt, but will be 1-2 feet longer and 1-2 feet wider to comply with more recent ADA requirements.



The original 1935-1936 front steps of the Fredericksburg Battlefield Visitor Center. The steps will be removed and replaced. Any damaged material will be replaced with in-kind materials and with in-kind design. To include railings and light poles.



The original 1935-1936 front steps of the Fredericksburg Battlefield Visitor Center. The steps will be removed and replaced. Any damaged material will be replaced with in-kind materials and with in-kind design. To include railings and light poles.



The original 1935-1936 front steps of the Fredericksburg Battlefield Visitor Center. The steps will be removed and replaced. Any damaged material will be replaced with in-kind materials and with in-kind design. To include railings and light poles.



The post-1965 plantings and vegetation will be removed and replaced with plantings that more reflect the original 1937 planting plan.



The post-1965 plantings and vegetation will be removed and replaced with plantings that more reflect the original 1937 planting plan.



Interior gutters on the Fredericksburg Battlefield Visitor Center. The visible temporary downspouts will be removed, and new exterior gutters and downspouts installed.



Four exterior gutters will be installed- two on the front of the two wings and two on the sides of the central portion – identified by red arrows. Two downspouts will be installed on the front of the building – one on each wing – identified by the blue arrows.



Four exterior gutters will be installed- two on the back of the two wings and two on the sides of the central portion – identified by red arrows. Two downspouts will be installed on the front of the building – one on each wing – identified by the blue arrows.



Downspouts will be undergrounded into existing storm water catch basins behind the building